



## SL-20 Sealer

- Easy to apply
- SL-20 is a dual-purpose acrylic sealer that cures (and seals) freshly placed concrete and refreshes existing concrete with a protective sheen
- UV-stable (non-yellowing)
- Easy to re-coat over worn sealer without having to strip surface

**WARNING:**  
Highly Flammable  
For Outdoor Use Only

# SL-20 Sealer

## Product Description

---

SL-20 is a dual-purpose acrylic sealer that cures (and seals) freshly placed concrete and refreshes existing concrete with a protective sheen. It improves concrete's resistance to water, salt, stains and dust. For outdoor use only.

## Storage

---

**WARNING: HIGHLY FLAMMABLE LIQUID.** Keep away from heat, sparks, high temperatures and open flames. Protect from freezing. Store in a cool, well-ventilated area between 50 °F and 90 °F (10 °C and 30 °C).

## Properties

---

Appearance: Clear to light-yellow liquid  
Density: 0.91 g/mL

Odor: Solvent  
pH: Not applicable

## Directions

---

**Surface Preparation:** Remove any previously applied sealers or composites (if necessary) with Interstar Sealer Remover (ISR) or an appropriate solvent (e.g., toluene, xylene). Clean the surface thoroughly; it must be completely clean, dry, and free of surface contaminants such as dust, dirt, and oils.

**Application:** SL-20 does not require any dilution. The temperature of the concrete should be above 50 °F (10 °C) before application. If used as a curing membrane, apply SL-20 when the concrete surface is completely dry. As a sealer, SL-20 should be applied only after the concrete has cured for a minimum of 28 days. Apply uniformly with a paint brush, roller or sprayer. Do not walk on the treated surface until the product is dry (4 to 6 hours).

**NOTE: FOR OUTDOOR USE ONLY.** Before sealing the entire surface, test on an inconspicuous area to be sure that the desired results can be achieved. If the application is too thick, it may cause yellowing of the sealer. In cool, humid conditions the color of freshly sealed concrete may not appear uniform and may show spots. As the concrete cures, the coloration will become even, though this can take up several months. SL-20 is **not** resistant to gasoline or to brake fluid.

**Coverage:** Approximately 245 – 320 ft<sup>2</sup>/gallon (6 – 7.5 m<sup>2</sup>/L).

## Safety

---

**WARNING: HIGHLY FLAMMABLE LIQUID. FOR OUTDOOR USE ONLY.** Avoid all contact with skin, eyes and clothing. Avoid breathing mists and vapors. Wear protective equipment when handling. Ensure adequate ventilation of the work area. Keep container tightly closed when not in use. For more information, please refer to the Product Safety Data Sheet (SDS).

## Availability

---

Interstar products are available throughout the United States, Canada, and Mexico. Please contact our Customer Service Department at (877) 693-1212 to place an order or to find a distributor in your area.